

### 1100 Hull

- White hull
- GRP sandwich construction hand laid
- Isophthalic gelcoat
- Isophthalic resin for outer layers
  Bulkheads laminated to hull and deck
- Waterline and cove line laid in the gelcoat
- Stringers and floors

### 1200 Deck

- White deck
- GRP sandwich construction
- Non-slip deck surface

### 1300 Steering system

- Rod link steering system
- Steering wheel with leather
- Semi-balanced, profiled rudder with alloy shaft and self aligning needle bearings

### 1400 Keel

- Lead keel with cast iron shaft with low centre of gravity, primered
- Deep draft: 1.98 m / 6'5", ballast weight approx.2.470 kg / 5,445 lb. (Option: Shoal draft 1.69 m / 5'5", ballast weight approx. 2.520 kg / 5,556 lb.; centre board 1.25 m / 4'1", ballast weight approx. 2.570 kg / 5,666 lb.)
- Stainless steel keel bolts

### 2000 Deck equipment

- Self draining anchor-locker with lockable hatch
- Self draining cockpit with large lockable storage
- 4 opening hatches in forward cabin, galley, head and saloon
- 11 acrylic glass windows with aluminium frames (7 opening)
- 4 mooring cleats
- 2 spring cleats
- 2 combined self tailing winches, halyard and jibsheet winches 40 STA
- 2 self tailing genoa winches 40 STA
- Halyards lead aft to cockpit
- 2 winch handles

measurements are approximate. Specification and material can be changed without notice. Greifswald, August 2004

٩I

- Bow fitting with integrated socket for gennaker pole and roller for Delta anchor 10 halyard stoppers Genoa tracks with cars and pin stops Pulpit with teak step Pushpit with ensign staff socket Sliding hatch garage Sliding hatch
- Drop board
- Double s. s. safety rail
- Teak handrails on deck
- Shear guard white plastic
- Cockpit shower
- Teak on cockpit seats
- Teak on cockpit bottom
- Swimming ladder

#### 3000 Technical system 3100 Plumbing + Fresh water Tanks:

Fresh water tank approx. 240 l Deck filler

### Pumps

Electric pressurised fresh water system Faucets:

Faucets in galley and head

### 3200 Grey water system **Bilge pumps**

1 electric bilge pump 1 manual bilge pump

### Head

1 manual marine toilet 1 holding tank with manual pump

and deck connector

### 3300 Engine

- Yanmar 3YM30, 21.3 kW/ 29 HP, inboard diesel engine
- Fresh water cooling
- 2-blade fixed prop
- Saildrive
- Fuel capacity approx. 80 l
- Fuel filter / water separator
- Filler on deck
- Seawater strainer
- Revolution counter
- Engine hour meter
- Insulated engine room

### **3400 Electrics**

12 V and 230 V circuits

### **Batteries**

- 2 batteries 12 V/70 Ah for engine and 12 V/100 Ah for service
- Main switch

# Electric control panel 12 V for

# onbord electrics

- Fuel and water tank gauges Voltmeter
- Electric panel 230 V
- With trip switch Outlet 230 V
- Separate switch for optional warm
- water heater

# **Interior lights**

- in forward cabin in aft cabin
- in saloon
- in galley
- in head
- in storage room

# Navigation lights

- Steaming light
- Bow light
- Stern light
- Anchor light

## **Navigation Instruments**

- Illuminated compass
- Echosounder
- Log

## 3500 Galley

- 2 stainless steel sinks
- 2-burner gas cooker with oven, gimbled
- Locker and drawers
- Insulated icebox with 12 V cooling unit Trash can

### 4000 Interior and accommodation Furniture:

- White bulkheads
- Mahogany faced plywood furniture
- Wooden door frames
- Wood doors with foam inside
- (sandwich construction)
- Locker doors partly with rattan
- Version 1: "Classic New England Style"
- Version 2: "Modern Mahogany Style" (Option)

### Cushions

For further information, please contact an authorised HANSE distributor.

- Version 1 Mattresses and cushions in blue material
- Version 2 Mattresses and cushions in yellow/white stripes (Option)

The Quality People in Yachting Yachtzentrum Greifswald GmbH & Co. KG Salinenstr. 22 · D-17489 Greifswald · Tel. +49 (0) 38 34 - 57 92 - 0 · Fax: +49 (0) 38 34 - 57 92 - 30 sales@hanseyachts.com · www.hanseyachts.com

## Forward cabin

- Separated from saloon by a door
- Large double-berth, 2.00 m / 6'6"
- Combined locker
  - Shelves above berth

# Aft cabin

- Separated from saloon by a door
- Large double berth, 2.00 m / 6'6"
- Locker
- Shelve
- 2<sup>nd</sup> aft cabin with double berth and locker, or separate shower (Option)

# Saloon

- Curved companionway steps
- U-shaped settee on star board
- Salon table with bottle storage
- Lockers and shelves
- Curtain rails
- approx. 1.89 m / 6'2" headroom

## Navigation area

- 2 single seats on port side (Option: bench)
- Chart table with storage between single seats

Shower with extendable hose and

Two spreader anodised aluminium

HANSE Single line reefing system

Stainless Steel standing rigging

Main and jib halyard lead aft to cockpit

Main sheet traveller on coachroof Main sail full batten with 2 reefs

Maindrop system with Lazy Jacks;

Selftacking jib with traveller

Electric switch panel

Holding tank

drain pump

5000 Rig + sails

9/10 - Rig

Rod kicker

Opening hatch

mast and boom

Roller furling gear

(cockpit handling)

Backstay adjuster

colour: "ecru"

Boom topping lift

Main and iib sheets

#### Head/Bath Marine toilet on port side

Sink